

However delay cells need to be added to correct the different circuit lengths between each VCO output to its respective counter. Every corrected delayed element is fed into independent and identical counters. The registers freeze the counters results for every time coded sequence (TCS). A given time clock is then obtained just by mathematical operations on the registered values.

3. RESULTS

A telecommunication link has been set from Inatel laboratory, at the town of Santa Rita do Sapucaí, Minas Gerais State, Brazil, to the transponder located at a high mountain top ("Manuela" mountain), with geodetic coordinates and altitudes well known in advance. The line-of-sight distance to the transponder was 4.8 km. The transit time on antennas is obtained for the pair of antennas on the link. An example of the measured total delay is given in Figure 2.




Fig. 2. Sample for the final clock reading obtained at the UART interface providing the total time delay that includes the propagation time in free space (ranging) and the delays produced by troposphere propagation and the electronic units. The readings are (in units of 10^{-6} s) accurate to one nanosecond.

We subtract the added delays (due to propagation in the troposphere, transmission cables, connectors, transmission and receiving equipments) from the free space propagation time on the well known path (i.e., of 32,032.45 ns). The Allan deviation for the whole set of measured data exhibits mid-term stability (at $\tau \leq 10^3$ seconds) approaching to good quality OCXO commercial oscillator (by a factor 3) [17], as well as to typical rubidium controlled crystal oscillator at $\tau \approx 10^4$ seconds (by a factor 3) [6]. Despite the technical distinction between the system presented here and the advanced GPS timing principles, the current single frequency L1 GPS mid-term stability are within the same order of magnitude (i.e. by a factor of about 6 at $\tau \approx 10^3$ seconds and a factor of about 3 at 10^4 seconds [6]). These results are particularly relevant considering they were obtained using standard transmitters, transponder and reception units, without any temperature control added.

The implementation of a fully operational Geolocal system brings the possibility to allow real-time independent determinations, to compare and provide support to other

systems (i.e., GPS and similarly conceived systems GLONASS, GALILEO, COMPASS) [17][18].

4. ACKNOWLEDGMENTS

This research is partially supported by the Brazilian agencies FINEP (federal) and FAPEMIG (state of Minas Gerais).

REFERENCES

- [1] J. Levine, "Introduction to time and frequency metrology", *Rev. Sci. Instrum.* **70**, 2567, 1999.
- [2] D.W. Allan, "Statistics of atomic frequency standard", *Proc. IEEE* **54**, 221-231, 1966.
- [3] T.A. Clark, R.M. Hambly and R. Abtahi, "Low cost, high accuracy GPS timing", *Proc. ION Navigation's GPS 2000 Conference*, Sept. 20, 2000 (see <http://www.gps-time.com/pub/IONGPS2000/ion-time>).
- [4] J. Mannerman, K. Kalliomaki, T. Mansten and T. Turunen, "Timing performance of various GPS receivers", *Proceedings of the 1999 Joint Meeting of the European Frequency and Time Forum and the IEEE International Frequency Control Symposium* (Besançon, France 13-16 April 1999), 287-290, April 1999.
- [5] A. Gifford, S. Pace and J. McNeff, "One-way GPS time transfer 2000", *Proc. 32nd. Annual Precise Time and Time Interval (PTTI) Meeting*, Reston, Virginia, USA, 28-30 Nov 2000.
- [6] T.A. Clark and R.H. Hambly, "Improving the performance of low cost GPS timing receivers", *38th Annual Precise Time and Time Interval (PTTI) Meeting*, Reston, Virginia, USA, 7 December 2006.
- [7] R.M. Hambly and T.A. Clark, "Critical evaluation of the Motorola 12+ GPS timing receiver vs. the master clock at U.S. Naval Observatory, Washington, DC", *34th Annual Precise Time and Time Interval (PTTI) Meeting*, 2-5 Dec. 2002, Reston, VA, 2002.
- [8] Lombardi, M.A. et al., "Time and frequency measurements using global positioning system", *Cal. Lab. Int. J. Metrology*, pp. 26-33, July-September, 2001.
- [9] P. L. Kaufmann et al., "Non recursive algorithm for remote geolocation using ranging measurements", *Math. Problems in Engineering*, v. 2006, pp. 1-9, Article ID79389, DOI:10.1155/MPE/2006/79389, 2006. <http://www.hindawi.com/GetArticle.aspx?doi=10.1155/MPE/2006/79389>.
- [10] "Sistema e Processo de Posicionamento Geográfico e Navegação", Brazil Patent PI 9101270, granted 30.09.1997, Filed 25.03.1991, and Brazil Addition Certificate CI 9101270, Filed 17.05.2002
- [11] "Geographic and space positioning system and process", Brazil Patent PI 03003968-4, Filed 08.10.2003, and International Patent Cooperation

Treaty PCT/BR2004/000190, Filed 04.10.2004.

- [12] D.I. Porat, "Review of sub-nanosecond time-interval measurements", *IEEE Trans. On Nucl.Sci.* **NS-20**, 36-51, 1976.
- [13] J. Kalisz, "Review of methods for time interval measurements with picosecond resolution", *Metrologia* **41**, 17-32, 2004.
- [14] C.N.M. Marins, P. Kaufmann, A.A. Ferreira Jr., P.H. Lopes, M.C. de Paiva, R.M. Villela and A.C. Silveira, "Precision clock and time transfer on a wireless telecommunication link", submitted, 2008.
- [15] Altera Corporation, PLLs & Clock Networks, Stratix II Device Handbook, v. 1, San Jose, CA, 2007.
- [16] See example of commercial oscillator time domain (Allan deviation) stabilities at EdRun Technologies website:
<http://www.edruntechnologies.com/pdf/OscOptions.pdf>
- [16] D. Wells, (editor), "Guide to GPS positioning", Canadian GPS Association, N. Brunswick, Canada, 1987.
- [17] M. Kayton (editor), Proc. IEEE Position Location and Navigation Symposium, 1988, reprinted from "*Navigation: Land, Sea, Air & Space*", , IEEE Press, Selected Reprint Series, IEEE Aerospace and Electronic System Society, New York, USA, 1990.